



PRODUCT DATA

LUBRIKO 53B

Lubriko 53B is a lithium complex lubricating grease formulated with 100% synthetic hydrocarbon fluids (PAO). This product has been formulated with a special additive package which insures high film strength, extreme pressure (EP) and anti-wear properties. In addition, this product has a high dropping point in excess of 500° F as well as exhibiting excellent low temperature performance to temperatures of -45°F (-43°C) to -50°F (-45°C).

TYPICAL PROPERTIES

NLGI Grade	2
Thickener Type	Lithium Complex
Texture	Smooth
Color	Light Blue
Worked Penetration, ASTM D 217, 77°F,	
60 strokes	265 - 295
Dropping Point, ASTM D 2265, °F Min.	500 (260)
Oxidation Stability, ASTM D 942, PSI	
Drop/100 hrs. Max	3.5
Rust & Corrosion, ASTM D 1743	Pass
Water Washout, ASTM D 1264, 175°F, %	5
Timken, ASTM D 2509, OK Load, Min	55
Four Ball EP, ASTM D 2596 Weld Pt. Kg Min.	315
Four Ball Wear, ASTM D 2266, Scar Dia. mm	0.60
Oil Separation, ASTM D 1742, Mass %, Max	10
Base Oil Viscosity:	
Viscosity Index, Min.	140
cSt @ 100°C	5.5-9.5
cSt @ 40°C	40 - 60

Information presented herein has been compiled from sources considered to be dependable and is accurate and reliable to the best of our knowledge and belief but is not guaranteed to be so. Nothing herein is to be considered as recommending and practice or any product in violation of any patent or in violation of any law or regulation. It is the user's responsibility to determine for himself the suitability of any material and, since conditions of use are not under our control, we must necessarily disclaim all liability and respect to the use of any material supplied by us. We are not responsible for the misuse and/or misapplication of our products.