



PRODUCT DATA

LUBRIKO AC2

Lubriko AC2 is an aluminum complex thickened lubricating grease formulated with highest quality base oils. Lubriko AC2 is fortified with extreme pressure and anti-wear additives as well as oxidation and corrosion inhibitors.

TYPICAL PROPERTIES

NLGI Grade.....	2
Soap Type.....	Aluminum Complex
Texture.....	Smooth
Color.....	Amber
Worked Penetration, ASTM D 217, 60 Strokes.....	265-295
Dropping Point, ASTM D 2265, °F Min.....	500
Oxidation Stability, ASTM D 942	
psi Drop 100 Hrs Max.....	5
Wheel Bearing Leakage, ASTM D 1263 Gms.....	5
Rust & Corrosion, ASTM D 1743.....	Pass
Water Washout, ASTM D 1264, 175°F, Max.....	5%
Timken, ASTM D 2509, OK Load, Min.....	45
Four Ball EP, ASTM D 2596	
Weld Point Kg, Min.....	315
LWI.....	40
Four Ball Wear, ASTM D 2266	
Scar Dia. mm, 40 Kg, Max.....	0.60

Base Oil Viscosity

SUS @ 100°F, 1000-1250

cSt @ 100°C, 14.5-16.5

cSt @ 40°C, 180-220

Viscosity Index 70 Min

Pour Point 0

Information presented herein has been compiled from sources considered to be dependable and is accurate and reliable to the best of our knowledge and belief but is not guaranteed to be so. Nothing herein is to be considered as recommending and practice or any product in violation of any patent or in violation of any law or regulation. It is the user's responsibility to determine for himself the suitability of any material and, since conditions of use are not under our control, we must necessarily disclaim all liability and respect to the use of any material supplied by us. We are not responsible for the misuse and/or misapplication of our products.