



PRODUCT DATA

LUBRIKO CW606B

Lubriko CW606B is a food grade aluminum complex thickened lubricating grease. It is formulated specifically for the food packaging and processing industry. Lubriko CW606B provides excellent extreme pressure and anti-wear protection and can be used over a wide range of operating temperatures.

NSF H1 Registered

TYPICAL PROPERTIES

NLGI Grade	2
Soap Type.....	Aluminum Complex
Texture	Smooth, Adhesive
Color	White
Worked Penetration, ASTM D 217,	
60 strokes.....	265-295
Dropping Point, ASTM D 2265, °F, Min	500
Bearing Corrosion, ASTM D 1743	Pass
Timken OK Load, Lbs. ASTM D 2509.....	40
Four Ball Wear, ASTM D 2266	
Scar diameter, mm. 0.60	
Four Ball EP, Weld Point, ASTM D 2596 Kgf.....	500
Copper Corrosion, ASTM D 4048.....	1b
Water Washout, ASTM D 1264, 175°F, % Loss.....	5
Roll Stability, ASTM D 1831, 2 Hrs, % Change Max.....	10

Oxidation Stability, ASTM D 942

PSI drop 100 hours, Max 5

PSI drop 500 hours, Max..... 10

Base Oil Viscosity

**SUS @ 100°F 340-355

**cSt @ 40°C..... 64-70

Flash Point, °F (°C) 430 (221)

Pour Point, °F.....-10

formation presented herein has been compiled from sources considered to be dependable and is accurate and reliable to the best of our knowledge and belief but is not guaranteed to be so. Nothing herein is to be considered as recommending and practice or any product in violation of any patent or in violation of any law or regulation. It is the user's responsibility to determine for himself the suitability of any material and, since conditions of use are not under our control, we must necessarily disclaim all liability and respect to the use of any material supplied by us. We are not responsible for the misuse and/or misapplication of our products.