



**PRODUCT DATA**

**LUBRIKO L206**

Lubriko L206 is a lithium 12 hydroxy lubricating grease formulated with the highest quality base oils available, and is fortified with rust and oxidation inhibitors as well as extreme pressure additives. This product has been formulated with a special additive package which insures high film strength, extreme pressure (EP) and anti-wear properties.

**Product Specifications**

NLGI Grade.....	2
Thickener Type.....	Lithium
Thickener %.....	7-9
Texture.....	Smooth
Color.....	Green
Worked Penetration, ASTM D 217, 77°F, 60 strokes.....	265-295
Dropping Point, ASTM D 2265, °F(°C)Min.....	350(177)
Wheel Bearing Leakage, ASTM D 4290,gm.Loss.....	5
Water Washout, ASTM D 1264, % Loss Max.....	10
Rust Prevention, ASTM D 1743, Rating.....	Pass
Copper Corrosion, ASTM D 4048, Rating.....	1b
Oxidation Stability, ASTM D 942, PSI Drop.....	5
Oil Separation, ASTM D 1742, % Loss.....	10
Four Ball Wear, ASTM D 2266, mm Scar Dia. ....	0.45
Four Ball EP Weld Point, ASTM D 2596.....	315
Four Ball Load Wear Index, ASTM D 2596.....	50
Base Oil Characteristics	
Viscosities:	
@ 100°C,cSt.....	11-15
@ 40°C,cSt.....	135-150
@ 100°F,SUS.....	700-850
Viscosity Index, Min.....	60

Information presented herein has been compiled from sources considered to be dependable and is accurate and reliable to the best of our knowledge and belief but is not guaranteed to be so. Nothing herein is to be considered as recommending and practice or any product in violation of any patent or in violation of any law or regulation. It is the user's responsibility to determine for himself the suitability of any material and, since conditions of use are not under our control, we must necessarily disclaim all liability and respect to the use of any material supplied by us. We are not responsible for the misuse and/or misapplication of our products.