



PRODUCT DATA

LUBRIKO M24

Lubriko M24 is a lithium 12-hydroxy lubricating grease formulated with the highest quality base oils available. Lubriko M24 is fortified with a special additive package, including rust and oxidation inhibitors as well as extreme pressure additives.

TYPICAL PROPERTIES

NLGI Grade.....	3
Thickener Type.....	Lithium
Thickener %	8-11
Texture	Smooth
Color	Amber
Worked Penetration, ASTM D 217, 60 strokes	220-250
Dropping Point, ASTM D 2265, °F (°C) Min.	350(177)
Wheel Bearing Leakage, ASTM D 4290, gm. Loss	5
Water Washout, ASTM D 1264, % Loss Max	10
Rust Prevention, ASTM D 1743, Rating.....	Pass
Copper Corrosion, ASTM D 4048, Rating.....	1b
Oxidation Stability, ASTM D 942, PSI Drop	5
Oil Separation, ASTM D 1742, % Loss	10
Four Ball Wear, ASTM D 2266, mm Scar Dia.....	0.50
Four Ball EP Weld Point, ASTM D 2596, Min.	250
Four Ball Load Wear Index, ASTM D 2596, Kgf.....	40
Timken OK Load, ASTM D 2509, LB.	40

Base Oil Characteristics

Viscosities:

@ 100°C, cSt 15.5-17.5

@ 40°C, cSt. 180-210

@ 210°F, SUS. 78.0-90.0

@ 100°F, SUS. 900-1100

Viscosity Index, Min. 88

Information presented herein has been compiled from sources considered to be dependable and is accurate and reliable to the best of our knowledge and belief but is not guaranteed to be so. Nothing herein is to be considered as recommending and practice or any product in violation of any patent or in violation of any law or regulation. It is the user's responsibility to determine for himself the suitability of any material and, since conditions of use are not under our control, we must necessarily disclaim all liability and respect to the use of any material supplied by us. We are not responsible for the misuse and/or misapplication of our products.