



PRODUCT DATA

LUBRIKO MPG

Lubriko MPG is a lithium 12 hydroxy lubricating grease formulated with the highest quality base oils available, and is fortified with rust and oxidation inhibitors as well as extreme pressure additives. This product has been formulated with a special additive package which insures high film strength, extreme pressure (EP) and anti-wear properties.

Product Specifications

NLGI Grade	2
Thickener Type	Lithium
Thickener %	7-9
Texture	Smooth
Color	Green
Worked Penetration, ASTM D 217, 77°F, 60 strokes	265-295
Dropping Point, ASTM D 2265, °F(°C)Min.	350(177)
Wheel Bearing Leakage, ASTM D 4290, gm.Loss	5
Water Washout, ASTM D 1264, % Loss Max.	10
Rust Prevention, ASTM D 1743, Rating	Pass
Copper Corrosion, ASTM D 4048, Rating	1b
Oxidation Stability, ASTM D 942, PSI Drop	5
Oil Separation, ASTM D 1742, % Loss	10
Four Ball Wear, ASTM D 2266, mm Scar Dia.	0.45
Four Ball EP Weld Point, ASTM D 2596	315
Four Ball Load Wear Index, ASTM D 2596.	50
Timken OK Load, ASTM D 2509, LB	50

Base Oil Characteristics

Viscosities:

@ 100°C,cSt. 11-15

@ 40°C,cSt. 135-150

@ 100°F,SUS..... 700-850

Viscosity Index, Min. 60

Information presented herein has been compiled from sources considered to be dependable and is accurate and reliable to the best of our knowledge and belief but is not guaranteed to be so. Nothing herein is to be considered as recommending and practice or any product in violation of any patent or in violation of any law or regulation. It is the user's responsibility to determine for himself the suitability of any material and, since conditions of use are not under our control, we must necessarily disclaim all liability and respect to the use of any material supplied by us. We are not responsible for the misuse and/or misapplication of our products.