



PRODUCT DATA

LUBRIKO UR2

Lubriko UR2 is a non-soap thickened polyurea lubricating grease formulated with high quality raw materials. It is fortified with rust and oxidation inhibitors as well as extreme pressure additives. Lubriko UR2 offers a dropping point of over 500°F. It performs well in areas wherewater washout is a major concern. The chemical and physical properties make it a superb all-purpose lubricating grease.

MEETS NLGI CERTIFICATION GC-LB.

TYPICAL SPECIFICATIONS

NLGI Grade	2
Thickener Type	Polyurea
Texture	Smooth
Color	Blue
Worked Penetration 60 strokes	265-295
Dropping Point ASTM D 2265, °F (°C) Min.	500(260)
Water Washout, ASTM D 1264, % Loss Max.	10.0
Rust Prevention, ASTM D 1743	Pass
Copper Corrosion, ASTM D 4048, Rating	1b
Oxidation Stability, ASTM D 942, PSI Loss, Max	5
Oil Separation, ASTM D 1742, % Loss, Max	5.0
Four Ball EP, Weld Point, ASTM D 2596, Min.	400
Load Wear Index, ASTM D 2596, Kgf.	50
Timken OK Load, ASTM D 2509, LB.....	60

Base Oil Characteristics

Viscosity

@ 100°C, cSt.....	13.5-15.5
@ 40°C, cSt.....	135- 155
@ 210°F, SUS.....	60.0-70.0
@ 100°F, SUS.....	625-725

Viscosity Index..... 70

Information presented herein has been compiled from sources considered to be dependable and is accurate and reliable to the best of our knowledge and belief but is not guaranteed to be so. Nothing herein is to be considered as recommending and practice or any product in violation of any patent or in violation of any law or regulation. It is the user's responsibility to determine for himself the suitability of any material and, since conditions of use are not under our control, we must necessarily disclaim all liability and respect to the use of any material supplied by us. We are not responsible for the misuse and/or misapplication of our products.